

HI-SPEED USB 2.0 2.5" DRIVE ENCLOSURE USER MANUAL

MODEL 703246




Thank you for purchasing the MANHATTAN® Hi-Speed USB 2.0 2.5" Drive Enclosure, Model 703246. This device will let you quickly and easily transfer, share and archive data, and expand storage capacities for desktop and notebook PCs. Among the drive enclosure's main features:


- Supports Hi-Speed USB 2.0 data transfer rates of up to 480 Mbps
- Lightweight, compact design requires no external power adapters for increased portability
- Sturdy aluminum case protects drive and facilitates cooling
- Fits standard 2.5" PATA (IDE) drives with easy, quick installation
- Windows and Macintosh compatible, Plug and Play, hot swappable
- Lifetime Warranty

SETTING UP THE DRIVE ENCLOSURE


NOTE: It's recommended that you first create a copy of your original data prior to connecting to the drive enclosure to prevent the possibility of data loss should a mistake be made during the setup procedure. MANHATTAN accepts no responsibility for lost data.




1. Remove the back cover from the enclosure.



2. Carefully connect your drive to the interface.



3. Re-insert your drive into the enclosure.



4. Replace and tighten the two screws to complete the procedure.

USB 2.0 Windows 98SE Installation

1. Place the installation CD in the CD-ROM drive.
2. Select "M110E-win98-driver" and double-click the Setup icon to run the program
3. With "Win98 USB Driver" displayed, click "Next."
4. Click "Finish" to restart the computer per the subsequent prompt.
5. After the restart, connect the drive enclosure to your computer. **IMPORTANT:** For proper power connections, plug the cable(s) into your computer first, then into the drive enclosure.

NOTE: For Windows Me/2000/XP/Vista/7, no need to install the additional driver: It's already installed.

Windows XP needs to be updated with SP2.

General

- 44-pin IDE internal connection
- Hi-Speed USB 2.0 mini B external connection
- M110E chipset
- DC power input jack 5 V / 1 A (AC adapter not included)
- Meets current Hi-Speed USB 2.0 & IDE/ATA133 standards
- USB cable, A-type male x 2 to mini B male, 1.2 m (4 ft.)
- 11.3 x 7.85 x 1.29 cm (4.45 x 3.09 x 0.51 in.)
- 70.5 g (2.48 oz.)

System Requirements

- Pentium 266 MHz or higher
- 64 MB RAM
- Windows 98SE/Me/2000/XP/Vista/7; MAC OS 9.0 and above

Package Contents

- Drive Enclosure
- USB cable
- Travel bag
- User manual



MANHATTAN® offers a complete line of PC Components,
Peripherals, Cables and Accessories. Ask your local computer dealer for more
information or visit us online at

www.manhattan-products.com

Copyright © MANHATTAN

All products mentioned are trademarks or registered trademarks of their respective owners.