

# HI-SPEED USB 2.0 EXTERNAL ENCLOSURE USER MANUAL

MODEL 703253



  
**MANHATTAN™**

MAN-703253-UM-0308-03

Thank you for purchasing the MANHATTAN® Hi-Speed USB 2.0, 3.5" External Enclosure, Model 703253.

These easy-to-follow instructions help make installation of the enclosure quick and simple, so you'll soon be enjoying the benefits of these features:

- Supports Hi-Speed USB 2.0 data transfer rates up to 480 Mbps
- Lightweight, compact design increases portability
- Sturdy aluminum case protects the drive and a built-in fan facilitates cooling
- Fits standard 3.5" PATA (IDE) drives with easy, quick installation
- Windows and Macintosh compatible, Plug and Play, hot swappable
- Power switch and LED indicator
- Lifetime Warranty


## INSTALLATION

**NOTE:** Before connecting the IDE drive, set it to Master mode. Make an extra copy of your original data prior to installation to avoid any data loss should a mistake be made during the procedure. (Otherwise, MANHATTAN cannot be held responsible for any lost data.)


1. Remove the 3.5" chassis from the enclosure.




2. Connect the 40-pin IDE cable and 12 V power cable to the HDD. Fix in place with the included screws.



3. Re-insert the chassis into the enclosure.



4. Tighten the screws on the back cover to complete the installation.



## Windows 98SE Driver Installation

1. Place the included driver CD in the CD-ROM drive and click on the file “M110E-win98-driver.”
2. Double-click the Setup icon to run the program.
3. When “Win98 USB Driver” displays, click “Next.”
4. When the “Restart my computer now!” prompt displays, click “Finish” to reboot. After the restart, connect the enclosure to your computer.

**NOTE:** Windows Me/2000/XP/Vista32/Vista64/Win7 already have the additional driver installed. Windows XP needs to be updated with SP2.

## SPECIFICATIONS

### Standards & Certifications

- Hi-Speed USB 2.0, USB 1.1, FCC, CE

### General

- Connections:
  - 40-pin IDE & 4-pin Molex internal
  - Hi-Speed USB 2.0 B-type external
- M110E chipset
- Internal cooling fan
- DC power input jack, 12 V / 2 A (AC adapter included)
- 22 x 12 x 3 cm (8.5 x 4.7 x 1.3 in.)
- 448 g (16 oz.)

### System Requirements

- Pentium 266 MHz or higher
- 64 MB RAM
- Windows 98/Me/2000/XP/Vista/7 or Mac 10.0.4-10.1.3 / 9.2.2 and above

### Package Contents

- External Enclosure with stand
- USB A-type male to B-type male cable, 1.2 m (4 ft.)
- AC power adapter with cable, 2.7 m (9 ft.)
- User manual, CD driver, screws



# MANHATTAN™

BRINGING COMPUTERS TO LIFE

MANHATTAN® offers a complete line  
of PC Components, Peripherals, Cables and Accessories.

Ask your local computer dealer for more information  
or visit us online at

**[www.manhattan-products.com](http://www.manhattan-products.com)**

Copyright © MANHATTAN

All products mentioned are trademarks or registered trademarks of their respective owners.