



Wireless 150N 3G Router

150 Mbps, 3G, 4-Port 10/100 Mbps LAN Switch

Part No.: **524940**

The Intellinet Network Solutions Wireless 150N 3G Router is the latest in wireless networking. Taking advantage of new technology, a wireless network can now see greatly enhanced network speeds and the convenience of 3G mobile technology.

Shares 3G / 3.5G Internet Connection

The Intellinet Network Solutions Wireless 150N 3G Router is a high-speed wireless 3G broadband router that supports both UMTS/HSDPA and EVDO networks. When connecting a 3G / 3.5G USB modem* to the router, all network (wired/wireless) users can share the 3G / 3.5G Internet connection. The Wireless 150N 3G Router can support 3G / 3.5G speed up to 7.2 Mbps.

Multiple Solutions in One Device

The Intellinet Network Solutions Wireless 150N 3G Router serves multiple purposes — an access point for your wireless network, a four-port router for hard-wiring Ethernet devices — and brings it all together so that the devices can access a high-speed Internet connection.

Automatic WAN Fail-Over

The Intellinet Network Solutions Wireless 150N 3G Router supports automatic WAN fail-over function. When connecting with DSL/cable broadband, the Wireless 150N 3G Router will enable the DSL/cable broadband connection automatically when a 3G / 3.5G Internet connection is not available. You can surf the Internet anywhere and anytime.

* For a complete list of compatible 3G USB modems, visit www.intellinet-network.com.

Features:

- Supports UMTS/HSDPA and EVDO 3G networks
- Up to 150 Mbps network link speed
- Complies with 2.4 GHz IEEE 802.11n standard and is backward compatible with IEEE 802.11g/b standards
- Supports WMM function to meet the multimedia data bandwidth requirement
- Supports Wi-Fi Protected Setup (WPS)
- Supports WAN connection auto fail-over
- Supports WEP and WPA/WPA2 (TKIP and AES) data encryption

- DHCP server supports static lease management
- Supports virtual server, port forwarding and DMZ (demilitarized zone)
- Supports DDNS (dynamic DNS)
- Supports UPnP (Universal Plug and Play)
- Integrated anti-DOS firewall
- QoS (Quality of Service) bandwidth management
- VPN Passthrough (PPTP/IPSec)
- Integrated USB 2.0 port for UMTS/HSDPA and EVDO 3G modems
- Use INTELLINET NETWORK SOLUTIONS Wireless N adapters for the best compatibility and performance
- Easy installation through Web-based user interface
- Three-Year Warranty

Specifications:

Standards

- IEEE 802.1d (Spanning Tree Protocol)
- IEEE 802.11b (11 Mbps Wireless LAN)
- IEEE 802.11g (54 Mbps Wireless LAN)
- IEEE 802.11n (150 Mbps Wireless LAN)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

General

- LAN ports: 4 RJ45 10/100 Mbps data ports
- LAN ports with Auto MDI/MDI-X
- WAN port: 10/100 Mbps RJ45 connector
- USB 2.0 port: 3G/3.5G USB modem
- Flash: 4 MB
- Memory: 16 MB SDRAM
- Certifications: FCC Class B, CE
- For a complete list of compatible 3G USB modems, visit www.intellinet-network.com

Router

- Supported WAN connection types:
 - 3G / 3.5G
 - Dynamic IP
 - Static IP
 - PPPoE
 - PPTP
 - L2TP
 - Telstra BigPond
- Protocols:
 - CSMA/CA
 - CSMA/CD
 - TCP/IP
 - UDP

- ICMP
- PPPoE
- NTP
- NAT
- DHCP
- DNS
- NAT:
 - Virtual server
 - Port forwarding
 - Special applications (port trigger)
- Firewall:
 - Access control based on MAC address
 - URL filter
 - DMZ (demilitarized zone)
- Supports UPnP (Universal Plug and Play)
- Supports DHCP (client/server)
- Supports WPS (WiFi Protected Setup)
- VPN passthrough: PPTP, IPSec protocol

Wireless

- Chipset: Ralink RT3050
- Wireless frequency range: 2.400 – 2.483 GHz
- Modulation technologies:
 - 802.11b: Direct Sequence Spread Spectrum (DSSS): DBPSK, DQPSK, CCK
 - 802.11g: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK, 16QAM, 64QAM
 - 802.11n: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK, 16QAM, 64QAM
- Channels:
 - USA & Canada: 11 channels
 - Europe: 13 channels
 - Japan: 14 channels
- Data rates:
 - IEEE 802.11b (11 Mbps, 5.5 Mbps, 2 Mbps, 1 Mbps)
 - IEEE 802.11g (54 Mbps, 48 Mbps, 36 Mbps, 24 Mbps, 18 Mbps, 12 Mbps, 9 Mbps, 6 Mbps)
 - IEEE 802.11n (MCS0-07: up to 150 Mbps)
- Output power:
 - OFDM: 15 dBm +/- 1 dBm (150 Mbps, 40 mW max.)
 - OFDM: 15 dBm +/- 1 dBm (54 Mbps, 40 mW max.)
 - CCK: 17 dBm +/- 1 dBm (11 Mbps, 63 mW max.)
- Receiver sensitivity:
 - 11n (150 Mbps) MCS0-07: 20 MHz: -73 dBm; 40 MHz: -68 dBm
 - 11g (54 Mbps) OFDM: -76 dBm
 - 11b (11 Mbps) CCK: -91 dBm
- Wireless security:
 - WEP encryption (64/128 bit)
 - WPA TKIP

- WPA2 AES
- WPA2 mixed
- WPA RADIUS
- Client access control through media access control (MAC) filter
- Fixed dipole antenna with 3 dBi gain

LEDs

- Power
- WLAN Link/Act
- LAN 1-4 Link/Act
- USB

Environmental

- Dimensions: 157 (W) x 127 (L) x 30 (H) mm (6.2 x 5.0 x 1.2 in.)
- Weight: 0.215 kg (7.58 oz.)
- Operating temperature: 10 – 40°C (50 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -20 – 60°C (4 – 149°F)

Power

- External power adapter: 12 V DC, 1.0 A
- Power consumption: 3.5 Watts max.

Package Contents

- Wireless 150N 3G Router
- User manual
- Power adapter
- Ethernet Cat5 RJ45 cable: 1.0 m (3 ft.)
- USB extension cable: 1.0 m (3 ft.)



