



# Wireless 150N 4-Port Router

150 Mbps, QoS, 4-Port 10/100 Mbps LAN Switch

Part No.: 524445 EAN-13: 0766623524445 | UPC: 766623524445

Wireless networking with three times the speed.

The INTELLINET NETWORK SOLUTIONS Wireless 150N Broadband Router is the latest in wireless networking. Taking advantage of new technology, a wireless network can now see greatly enhanced network speeds.

#### **Multiple Solutions in One Device**

The INTELLINET NETWORK SOLUTIONS Wireless 150N Broadband Router serves multiple purposes — an access point for your wireless network, a 4-port router for hard-wiring Ethernet devices — and brings it all together so that the devices can access a high-speed Internet connection.

#### **Features:**

- Up to 150 Mbps network link speed
- Complies with 2.4 GHz IEEE 802.11n standard and is backward compatible with IEEE 802.11g/b standards
- Supports WMM function to meet the multimedia data bandwidth requirement
- Supports Wi-Fi Protected Setup (WPS)
- Supports WEP and WPA/WPA2 (TKIP and AES) data encryption
- Integrated 10/100 Mbps LAN switch with Auto MDI/MDI-X support
- Easy Internet setup through WAN connection wizard
- DHCP server assigns IP addresses for all LAN users
- DHCP server supports static lease management
- Supports virtual server, port forwarding and DMZ (demilitarized zone)
- Supports DDNS (dynamic DNS)
- Supports UPNP (Universal Plug and Play)
- Integrated anti-DOS firewall
- QoS (Quality of Service) bandwidth management



- VPN Pass Through (PPTP, IPSec, L2TP)
- Use INTELLINET NETWORK SOLUTIONS Wireless N adapters for the best compatibility and performance
- Easy installation through Web-based user interface
- System status
- Security log
- Firmware upgradeable
- Three-Year Warranty

## Specifications:

Standards

- IEEE 802.1d (Spanning Tree Protocol)
- IEEE 802.11b (11 Mbps Wireless LAN)
- IEEE 802.11g (54 Mbps Wireless LAN)
- IEEE 802.11n (150 Mbps Wireless LAN)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

## General

- LAN ports: 4 RJ45 10/100 Mbps data ports
- LAN ports with Auto MDI/MDI-X
- WAN port: 10/100 Mbps RJ45 connector
- LAN to WAN throughput: 93 Mbps
- Flash: 2 MB
- Memory: 16 MB SDRAM
- Certifications: FCC Class B, CE, RoHS

## Router

- Supported WAN connection types:
- Dynamic IP (DHCP for cable service)
- Static IP
- PPPoE (for DSL)
- PPTP
- Protocols:
- CSMA/CA
- CSMA/CD
- TCP/IP
- UDP
- ICMP
- PPPoE
- NTP
- NAT (network address translation)
- DHCP
- DNS
- NAT:
- Virtual server



- Port forwarding
- Special applications (port trigger)
- Firewall:
- Access control-based on MAC address
- URL filter
- DMZ (demilitarized zone)
- Supports UPNP (Universal Plug and Play)
- Supports DHCP (client/server)
- Supports PPPoE (DSL), DHCP (cable) and static IP
- Supports VPN PPTP, L2TP and IPsec passthrough

### Wireless

- Wireless frequency range: 2.400 2.483 GHz
- Modulation technologies:
- 802.11b: Direct Sequence Spread Spectrum (DSSS): DBPSK, DQPSK, CCK
- 802.11g: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK, 16QAM, 64QAM
- 802.11n: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK,
- 16QAM, 64QAM
- Channels:
- USA & Canada: 11 channels
- Europe: 13 channels
- Japan: 14 channels
- Data rates:
- IEEE 802.11b (11 Mbps, 5.5 Mbps, 2 Mbps, 1 Mbps)
- IEEE 802.11g (54 Mbps, 48 Mbps, 36 Mbps, 24 Mbps, 18 Mbps, 12 Mbps, 9 Mbps, 6 Mbps)
- IEEE 802.11n (MCS0-7: up to 150Mbps)
- Output power:
  - OFDM: 12 dBm +/- 1.5 dBm (150 Mbps)
  - OFDM: 12 dBm +/- 1.5 dBm (54 Mbps)
- CCK: 16 dBm +/- 1.5 dBm (11 Mbps)
- Receiver sensitivity:
- 11n (150 Mbps) MCS7: 20 MHz: -64 dBm; 40MHz: -61 dBm
- 11g (54 Mbps) OFDM: -65 dBm
- 11b (11 Mbps) CCK: -76 dBm

• Maximum coverage distance: 100 m / 328 ft. (indoors), 300 m / 980 ft. (outdoors)

- Wireless security:
- WEP encryption (64/128 bit)
- WPA TKIP
- WPA2 AES
- WPA2 mixed
- WPA RADIUS
- Client access control through media access control (MAC) filter
- Fixed dipole antenna with 2 dBi gain



LEDs

- Power
- WLAN Link/Act
- LAN 1-4 Link/Act

### Environmental

- Dimensions: 157 (W) x 127 (L) x 30 (H) mm (6.2 x 5.0 x 1.2 in.)
- Weight: 0.8 kg (1.7 lbs.)
- Operating temperature: 0 40°C (32 104°F)
- Operating humidity: 10 90% RH, non-condensing
- Storage temperature: -20 60°C (4 149°F)

#### Power

- External power adapter: 5 V DC, 1.0 A
- Power consumption: 2.3 Watts max.

Package Contents

- Wireless 150N 4-Port Router
- User manual
- Power adapter
- Ethernet Cat5 RJ45 cable: 1.0 m (3 ft.)







For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com. All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.