



1-Port USB Wireless Print Server

802.11g, Single USB Printer Port

Model
509060

Print server support through a wired or wireless network.

The INTELLINET NETWORK SOLUTIONS™ 1-Port USB Wireless Print Server allows users to share a printer through either a wired or wireless network (10/100 Mbps and/or 802.11 b/g wireless).

Easy Installation and Configuration

The USB Wireless Print Server's easy-to-use installation wizard allows for quick setup to the print server. The print server can also be conveniently configured from any network client that supports Web browsing.

Supports Peer-to-Peer and Server-Based Printing

Users can connect directly with the USB Wireless Print Server to execute printing jobs (peer-to-peer printing), or can send print jobs first to a server and then allow the server to connect with the print server to execute the printing jobs.

Provide Complete Printing Methods

The USB Wireless Print Server provides LPR, IPP, SMB/TCP, Raw Printing and Unix Logical printing methods. You can choose the best printing method according to your environment.

Supports Major Operating Systems

The USB Wireless Print Server is compatible with all major operating systems used today (Windows 98SE/Me/NT/2000/XP/Vista), NetWare (3.x above), MAC OS and Unix/Linux.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all INTELLINET NETWORK SOLUTIONS products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.





Model
509060

Features

- Connects any USB printer to the network
- Works with any access point or peer-to-peer wireless network
- 802.11g (54 Mbps Wireless) compliant
- Detachable antenna (RP-SMA connector)
- Go wired or wireless — Includes 10/100 Mbps Ethernet network port connection
- USB printer port connection
- Compatible with all major operating systems (Windows 2000/XP/2003/Vista (32-bit/64-bit), MAC OS and Unix/Linux)
- Reset button
- LAN, Status and WLAN LEDs
- Pocket size fits into portable tool kits
- Lifetime Warranty

Specifications

GENERAL

- CPU: MIPS CPU (240 MHz)
- Flash: 2 MB NOR Flash
- RAM: 16 MB SDRAM
- Printer port: USB 2.0 type A x 1
- LAN port: 10/100M UTP port x 1 (Auto-MDI/MDI-X)
- Antenna: external 2 dBi dipole antenna
- Output power: 16 - 18 dBm
- Power: 5 V DC, 1 A power adapter
- Dimensions: 20 (H) x 58 (W) x 82 (D) mm
- Temperature: 0 - 55°C
- Humidity: 10 - 90% (non-condensing)
- Certification: FCC, CE class B

PACKAGE CONTENTS

- Wireless Print Server
- Detachable antenna
- Power adapter
- Utility CD (software & user manual)
- Quick start guide

For more information on INTELLINET NETWORK SOLUTIONS products, consult your local dealer or visit www.intellinet-network.com.



Copyright © INTELLINET NETWORK SOLUTIONS